

EC SERIES

DESCRIPTION

**EC SERIES EC-12/EC-15/EC-215/EC-18**

**Product Type:**The EC-12 and EC -15 are satellite loudspeakers,wide-range loudspeaker system two-way/two-speaker,medium power,long/throw built-passive filter.high efficiency.The EC-215 is a portable,dual fifteen-inch.two-way speaker system designed for reinforcement of music and speech.The EC-18 is SUB bass loudspeakers system,high efficiency,medium power system for the reproduction of low frequencies.

**APPLICATION**

- Live club performance
- Karaoke applications
- Premium club installations

Technical Information

**Model EC-12**

Power rating	250W(RMS)
Sensitivity(1W/1M)	96db
Impedance	8Ω
Frequency Response(-3db)	58Hz~18KHz
Dispersion HxV	90° × 60°
Loudspeaker and Loading	LF:1 × 12"High pass vented box HF:1 × 1"Exit horn loaded
Weight	23kg
Dimension(W × D × H)	370 × 400 × 660mm
Packing (W × D × H)	455 × 480 × 770mm

Technical Information

**Model EC-15**

Power rating	300W(RMS)
Sensitivity(1W/1M)	96db
Impedance	8Ω
Frequency Response(-3db)	58Hz~18KHz
Dispersion HxV	90° × 60°
Loudspeaker and Loading	LF:1 × 15"High pass vented box HF:1 × 1"Exit horn loaded
Weight	30kg
Dimension(W × D × H)	450 × 480 × 740mm
Packing (W × D × H)	545 × 570 × 850mm

**Model EC-215**

Power rating	600W(RMS)
Sensitivity(1W/1M)	99db
Impedance	4Ω
Frequency Response(-3db)	50Hz~18KHz
Dispersion HxV	90° × 60°
Loudspeaker and Loading	LF:2×15"High pass vented box HF:1×1"Exit horn loaded
Weight	45kg
Dimension(W×D×H)	500×515×1210mm
Packing (W×D×H)	590×605×1310mm

**Model EC-18**

Power rating	400W(RMS)
Sensitivity(1W/1M)	98db
Impedance	8Ω
Frequency Response(-3db)	45Hz~1150KHz
Dispersion HxV	Quasi-omnidirectional
Loudspeaker and Loading	LF:1×18"High pass vented box HF:/
Weight	38kg
Dimension(W×D×H)	550×700×660mm
Packing (W×D×H)	650×800×770mm