MP SERIES

DESCRIPTION

MP SERIES MP-112/MP-115/MP-225

Product The **MP** Series consists of the **MP-112,MP-115,MP-225.**The **MP-112** and **MP-115** are wide-range compact loudspeakers system, two-way/two-speaker high power, long/short throw with built-in passive filter. The **MP-225** is wide-range compact loudspeakers System, two-way/three-speaker,high power, long/short throw with built-in passive filter

APPLICATION

- Live sound reinforcement
- Touring and installed applications
- Special effects sub-bass

MP-112

MP-115

MP-225

SPECIFICATIONS	MP-112	MP-115	MP-225
Power-Watts	300W(RMS)	500W(RMS)	1000W(RMS)
Sensitivity(dBSPL 1W/1M)	96dB(1W/1M)	97dB(1W/1M)	99dB(1W/1M)
Impedance (ohms)	8Ω	8Ω	4Ω
Frequency Response	58Hz~20kHz	50Hz~20kHz	45Hz~20kHz
Average Dispersion	90° ×80°	90° ×80°	90° ×80°
Loudspeaker and Loading			
LF	1×12" High pass vented box	1×15" High pass vented box	2×15"High pass vented box
HF	1×1" Exit horn loaded	1×1" Exit horn loaded	1×1" Exit horn loaded
Weight(Kg)	25Kg	35Kg	58Kg
Dimensions (WxDxH)	370×375×660mm	490×510×800mm	490×510×1210mm
Packing (WxDxH)	530×530×770mm	585×605×910mm	585×605×1320mm