B SERIES

DESCRIPTION

B SERIES B-12/B-15/TM-18.1

PHYSICAL PROPERTIES

●**Product Type**: The **B-12** and **B-15** are wide-range compact loudspeakers system, two-way /two-speaker, medium power, short throw with built-in passive filter. The **TM-18.1** is SUB bass loudspeakers, high efficiency, high power system for the reproduction of low frequencies.

●**Enclosure Material and Finish**: Asymmetric enclosure in 18mm MDF or plywood with internal bracing, and rounded corners. Gray ultra thane paint.

●**Standard Accessories**: Steel grill, handles internal support tube/stand housing; flying points with nut plates, Speakon NL4FC connector.

●**Connectors**: 2 X NL4 speakon in parallel
LF and HF Pin 1+,2+ pos; Pin 1-,2- neg(not include MX-8)

APPLICATION

●Live sound reinforcement
●Bars, clubs and theaters etc.
●Special effects sub-bass

B-12

B-15

TM-18.1

SPECIFICATIONS	B-12	B-15	TM-18.1
Power-Watts	250W（RMS）	450W（RMS）	600W（RMS）
Sensitivity(dBSPL 1W/1M)	96dB（1W/1M）	97dB（1W/1M）	98dB（1W/1M）
Impedance (ohms)	8Ω	8Ω	8Ω
Frequency Response	50Hz～19kHz	40Hz～19kHz	50Hz～260Hz
Average Dispersion	90°× 60°	90°× 60°	Quasi-omnidirectionals
Loudspeaker and Loading			
LF	1×12"	1×15"	1×18"
	High pass vented box	High pass vented box	High pass vented box
HF	1×1" Exit Horn loaded	1×1" Exit Horn loaded	/
Weight(Kg)	18Kg	23Kg	50 Kg
Dimensions (WxDxH)	358x368x585mm	440x460x725mm	610x510x700mm
Packing (WxDxH)	438x448x665mm	520x540x805mm	700x590x780mm