

F SERIES

FEATURES

F SERIE F-10/F-12/F-15/F-215/S-18/S-218

PHYSICAL PROPERTIES

Product Type: The **F Series** are different from the FB Series that features higher quality components. The **F-10,F-12,F-15** and **F-215** are wide-rang compact loudspeakers system, two-way/two-speaker, high power, short throw with built-in passive filter. And the **S-18, S-218** are **SUB** bass loudspeakers system, high efficiency, high power system for the reproduction of low frequencies.

Enclosure Material and Finish: Asymmetric enclosure in 15 or 18mm plywood and MDF with internal bracing, rounded corners, integral handles and rotating speaker baffle. Gray ultra thane paint.

Standard Accessories: Steel grill, 2 handles internal support tube/stand housing; flying points with nut plates, Speakon NL4FC connector.

Connectors:2×NL4 speakon in parallel

LF and HF Pin 1+2+pos;Pin 1-2-neg

DESCRIPTION

Live club performance

Bars, restaurants and theatres etc

Installed applications

Special effects sub-bass

Model:F-10

Power-Watts	300W(RMS)/750W(PGM)
Sensitivity(dBSPL 1W/1M)	97dB(1W/1M)
Impedance (ohms)	8Ω
Frequency Response	50Hz~19kHz
Average Dispersion	90° × 60°
Loudspeaker and loading	LF :1×10” High pass vented box HF: 1×1” Eixt horn loaded
Weigh(Kg)	16.2Kg
Dimensions (W×D×H)	355×315×500mm
Packing (W×D×H)	430×390×580mm

Model:F-12

Power-Watts	400W(RMS)/1000W(PGM)
Sensitivity(dBSPL 1W/1M)	98dB(1W/1M)
Impedance (ohms)	8Ω
Frequency Response	45Hz~20kHz
Average Dispersion	90° × 60°
Loudspeaker and loading	LF :1×12” High pass vented box HF: 1×1” Eixt horn loaded
Weigh(Kg)	19Kg
Dimensions (W×D×H)	405×367×573mm
Packing (W×D×H)	480×450×655mm

Model:F-15

Power-Watts	500W(RMS)/1250W(PGM)
Sensitivity(dBSPL 1W/1M)	99dB(1W/1M)
Impedance (ohms)	8Ω
Frequency Response	35Hz~20kHz
Average Dispersion	90° × 60°
Loudspeaker and loading	LF :1×15” High pass vented box HF: 1×1.5” Eixt horn loaded
Weigh(Kg)	31.5Kg
Dimensions (W×D×H)	475×443×690mm
Packing (W×D×H)	555×525×770mm

Model:F-215

Power-Watts	1000W(RMS)/2500W(PGM)
Sensitivity(dBSPL 1W/1M)	102dB(1W/1M)

Impedance (ohms)	4Ω
Frequency Response	40Hz~20kHz
Average Dispersion	90° × 60°
Loudspeaker and loading	LF : 2 × 15" High pass vented box HF: 1 × 1.5" Eixt horn loaded
Weigh(Kg)	53Kg
Dimensions (W × D × H)	556 × 496 × 1076mm
Packing (W × D × H)	636 × 576 × 1161mm